

# 98cm Flyaway Antenna Terminal

## Eagle Mount Series



- Three piece antenna terminal assembly: reflector, pedestal and boom arm.
- Transit Cases:  
Reflector-Soft or Hard Case  
Mount-Soft or Hard Case
- One or two piece lightweight composite reflector
- Stainless steel hardware for excellent corrosion resistance
- Captive Hardware
- Anodized Pedestal
- Same antenna optics as standard VSAT products
- Transceiver Agnostics
- Meets or exceeds regulatory agency requirements
- Available Ka and Ku Band RF components
- Available Accessories; GPS, Compass, Stakes, RF Cables



### RF Performance

MODEL#	98138	98158
	Ku-Band	Ka-Band
Effective Aperture	98cm (38 in)	98cm (38 in)
Operating Frequency	Tx . . . . . 13.75 - 14.50 GHz . . . . .	.28.00 - 30.00 GHz
	Rx . . . . . 10.70 - 12.75 GHz . . . . .	.18.10 - 20.20 GHz
Polarization	. . . . . Linear, Dual . . . . . Linear or Circular	
Gain (± 0.2 dB)	Tx . . . . . 41.5 dBi @ 14.3 GHz. . . . .	47.6 dBi @ 30.0 GHz
	Rx . . . . . 40.0 dBi @ 12.0 GHz. . . . .	44.1 dBi @ 20.2 GHz
Cross Polarization	Tx . . . . . 30dB 1dB contour . . . . .	circular. . . 25dB
	Rx . . . . . 30dB 1dB contour . . . . .	circular. . . 22dB
Antenna Noise Temperature	10° Elevation . . . . .	60K. . . . . 88K
	20° Elevation . . . . .	50K. . . . . 62K
	30° Elevation . . . . .	45K. . . . . 51K
3dB Beamwidth	Tx . . . . . 1.5° @ 14.3 GHz . . . . .	0.69° @ 30.0 GHz
	Rx . . . . . 1.8° @ 12.0 GHz. . . . .	1.01° @ 20.2 GHz
Isolation (Port to Port)	Tx . . . . . 90dB . . . . .	.90dB
	Rx . . . . . 40dB . . . . .	.80dB
Output Waveguide Interface Flange	Tx . . . . . WR75 . . . . .	WR28
	Rx . . . . . WR75 . . . . .	WR42
Sidelobe Envelope (Tx, Co-Pol dB)	100 λ/D < Θ < 20° . . . . .	29 - 25 Log Θ dB
	20° < Θ < 26.3° . . . . .	-3.5 dB
	26.3° < Θ < 48° . . . . .	32-25 Log Θ dB
	48° < Θ < 180° . . . . .	-10 dB (averaged)
VSWR	1.3:1 Max . . . . .	1.2:1 Max

### Mechanical Performance

Reflector Material	. . . . . One-Piece Lightweight Composite	
Optional.	. . . . . Two-Piece Lightweight Composite	
Mount Type.	. . . . . Elevation over Azimuth	
Maximum Radio Weight	. . . . . 3.6kg or 8lb for RF Electronics	
Elevation Adjustment Range	. . . . . .5° - 90° Continuous, ±5° Fine	
Azimuth Adjustment Range	. . . . . 360° Continuous, ±5° Fine	
Wind Loading.	Operational (without ballast)	. . . . . 48km/h (30 mph)
	With Ballast (with staking)	. . . . . .96 km/h (60 mph)
Temperature	. . . . . -30°C to 60°C	
Humidity	. . . . . 0 to 100% (Condensing)	
Rain	Operational . . . . .	4" / hr (10cm / hr)
	Survival . . . . .	6" / hr (15cm / hr)
Solar Radiation.	. . . . . 360 BTU/h/ft2	
Weight Without Case.	Mechanism . . . . .	35 lbs
	Reflector . . . . .	19 lbs
Weight With Case	. . . . . 90 lbs	
Transit Case	Reflector . . . . .	46.00" x 11.25" x 31.25"
	Mount . . . . .	43.00" x 19.00" x 17.00"

1315 Outlet Center Drive, Smithfield NC 27577

REV 09/19 - 07

T + 1 (919) 934-9711 F + 1 (919) 989-2274 Sales@skywareglobal.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice. © 2019 Global Skyware