



## Sat-Light Platinum Series

# PL7632 IF RF Splitter/Combiner



### Features & Benefits

- Reduces cable connector failures
- Greatly improves cable management
- High performance

### Product Description

Global Foxcom's Sat-Light/Platinum's **PL7632 IF RF Splitter / Combiner** is a high performance, passive, 2way unit that combines or splits optical signals.

# Sat-Light Platinum Series

## Specifications

RF Specifications	Units	Typical	Minimum	Maximum
Frequency Range	MHz		10	200
Insertion Loss (Above 3dB)	dB			3.5
Isolation			30	
Ripple [in band]	dB			±0.4
Input/Output Return loss	dB			-23
RF Connector (Input/Output)	Type	FC/APC, SC/APC [E2000 option]		
DC Passing		No		
Power Passing	mA			
<b>Physical Specifications</b>				
Operating Temperature Range	°C		-10	+55
Storage Temperature Range	°C		-45	+85
Relative Humidity	95% non-condensing			
Altitude	ft / Km	10,000 [3.08 ] operating <sup>1</sup> 14,000 [12.2] non-operating		
Dimensions [D×W×H]	ins/cm	12×0.8×4 / 30.5×2×10.2		
Weight	lbs./Kg	0.5 / 0.23		
<b>Physical / Environmental Specifications</b>				
Shock & Vibration	Designed for normal transportation environment per section 514.4 MIL-STD-810E. Designed to withstand 20G at 11 ms [½ sine pulse] in non-operating configuration.			

1. With standard adiabatic derating of 2°C/1000 ft. [0.3 Km]  
All specifications are subject to change without notice.

## Ordering Information

Model	RF Connector Type	Description
PL7632	-75F	75-Ohm F
	-75BNC	75-Ohm BNC
	-50BNC	50-Ohm BNC
	-50SMA	50-Ohm SMA
	-50N	50-Ohm N