



Sat-Light Gold Series

GL7220-Long Distance L-Band Optical Downlink



Features & Benefits

- Optimized for Professional Satellite and Wireless Applications
- Up to 40Km Transmission Distance
- Selectable VAR/AGC/MGC
- Front Panel Test Port
- Selectable LNB Powering
- Powerful Monitoring Features
- Compatible with all 1st Generation Sat-Light Products

Product Description

Global Foxcom's Sat-Light/Gold L-Band Interfacility Link offers a high performance, cost effective alternative to conventional coaxial-cabled systems. The Gold L-Band IFL covers the range of 950 to 2200MHz. The Gold Series L-Band link is designed for a wide range of satellite power levels. Global Foxcom's high dynamic range DFB laser delivers exceptional signal quality for the most demanding applications.

The Gold series is compatible with first generation Sat-Light 7000 Series platform. The Gold Series support L-Band, 70/140MHz IF, Wideband (10-2200 MHz), 10MHz Reference, Redundancy, M & C, SNMP, Ethernet, and Serial Data Communication.

The link consists of an optical transmitter, which receives the RF signal from an LNB or LNA, and an optical receiver that connects to the indoor receiver equipment. All satellite modulation schemes are accommodated – digital or analog. Inherently low phase is achieved by direct modulation of the laser diode.

Sat-Light Gold Series

Specifications

GL7220 L-Band Optical Downlink [950-2200MHz], 16dB Optical Budget

RF Specifications	Units	Typical	Minimum	Maximum
Frequency Range	MHz	950-2200MHz		
Link Gain	dB	Adjustable	-10	+10
Amplitude Response @ Unity Gain 950-2200MHz any 36 MHz	dB	±.2 ±0.25		±2.2 ±0.3
Gain Stability @ Constant Temp	dB/24hr	±0.25		±0.3
SFDR ¹	dB/Hz ^{2/3}		88	
CNR [any 36 MHz] ¹	dB	43	40	
Noise Figure (NF) ¹	dB	22		21
Output IP3 (OIP3) ²	dB	+5	0	
Third Order Inter-Modulation [IMD] ³	dBc	Adjustable	55	30
Group Delay Variation- linear: 950-2200MHz	ns	4		5
Input Signal Range – Total Power	dBm		-45	-20
RF Output Signal Range – Total Power	dBm		-45	-20
Maximum Input without damage	dBm		+15	
Input/Output Impedance (75 or 50)	Ohm			
TX/RX Input/Output VSWR 50 Ohm 75 Ohm	dB	-14 -12		-14 -12
RF Connector Type: Input/Output Test Port		F, SMA BNC		
Test Port [front panel sample port]	dB	-20	-22	-18
Optical Specifications	Units	Typical	Minimum	Maximum
Optical Power Output	dBm	3	1	4
Optical Budget / Distance	dB/Km	1310nm 1550nm / 16dB 40Km		
Optical Connector Types		FC/APC or SC/APC		
Optical Wavelength	nm	1310/1550/CWDM		
Electrical Specifications	Units	Typical	Minimum	Maximum
Supply Voltage	Vdc	13	12.7	18
Supply Current [TX] ⁴	Amps	0.4		
Supply Current (RX)	Amps	0.3		
Physical Specifications	Units	Typical	Minimum	Maximum
Operating Temperature Range			-10	+55
Dimensions [D×W×H]		RX: 5" x 5" x 1.5" TX: 5" x 5" x 3"		
MTBF	Hours	RX: 359,057 TX: 309, 481		

1. -50dBm RF in, 20dB gain, IMD=-40dBc @ 16dB Opt Budget

3. User adjustable

2. -25dBm RF Output, IMD=-40dBc

4. Under 10°C add 120 mA [laser heating]

Ordering Information

GL7220T – Gold L-Band Downlink Transmitter

GL7220R16– Gold L-Band Downlink Receiver